


PW20H Potable Water Suction and Delivery Hose



Construction:

Tube: White NR.

Reinforcement: High Tensile Textile Cords with Embedded Steel Helix Wire.

Cover: Orange NBR/PVC Blend; Abrasion, Ozone and Hydrocarbon Resistant.

Temperature Range: -35°C To +100°C.

Typical Application: Potable Water Transfer.

Branding:

Continental ContiTech **PW20H POTABLE WATER SUCTION & DELIVERY WP 20 BAR**

White text

Technical Data:

Part No	Inside Dia		O.D. mm	Working Pressure		Minimum Burst Pressure		Min Bend Rad mm	Weight Kg/M
	mm	Inch		Bar	PSI	Bar	PSI		
PW20H-032	51	2	70	20	300	80	1200	305	2.70
PW20H-048	76	3	99	20	300	80	1200	380	4.90
PW20H-064	102	4	127	20	300	80	1200	510	6.86
PW20H-080	127	5	155	20	300	80	1200	635	11.00
PW20H-096	152	6	182	20	300	80	1200	760	15.40
PW20H-128	203	8	236	15	225	60	900	1015	20.00

Dunlop Oil & Marine Ltd
Jubilee Industrial Estate
Ashington, Northumberland
NE63 8UB United Kingdom
www.dunlop-oil-marine.co.uk

Continental 
CONTITECH

The content of this publication is not legally binding and is provided as information only. The trademarks displayed in this publication are the property of Continental AG and/or its affiliates. Copyright © 2011 ContiTech AG. All rights reserved.
For complete information go to:
www.contitech.de/discl_en