


# CX16H Chemical Suction and Delivery Hose



## Construction:

**Tube:** Black Conductive EPDM Blend.

**Reinforcement:** Textile Braided, Copper Static Wire, Zinc Plated Steel Wire Helix.

**Cover:** CR, Black Conductive; Abrasion, Oil and Ozone Resistant.

**Temperature Range:** -30°C To +85°C.

**Typical Application:** Acid and Chemical suction and delivery suitable for 98% of existing Chemicals.

## Branding:

**Continental ContiTech CX16H CHEMICAL SUCTION & DELIVERY WP 16 BAR**

White text on a Purple stripe

## Technical Data:

Part No	Inside Dia		O.D.	Working Pressure		Minimum Burst Pressure		Min Bend Rad	Weight
	mm	Inch		Bar	PSI	Bar	PSI		
CX16H-016	25	1	37	16	232	64	928	260	1.00
CX16H-024	38	1½	51	16	232	64	928	400	1.60
CX16H-032	51	2	67	16	232	64	928	550	2.40
CX16H-048	76	3	91	16	232	64	928	800	3.10

Dunlop Oil & Marine Ltd  
Jubilee Industrial Estate  
Ashington, Northumberland  
NE63 8UB United Kingdom  
[www.dunlop-oil-marine.co.uk](http://www.dunlop-oil-marine.co.uk)

**Continental**   
**CONTITECH**

The content of this publication is not legally binding and is provided as information only. The trademarks displayed in this publication are the property of Continental AG and/or its affiliates. Copyright © 2011 ContiTech AG. All rights reserved.  
For complete information go to:  
[www.contitech.de/discl\\_en](http://www.contitech.de/discl_en)