

Cementing Hose

Standard

API Spec. 7K FSL O

Construction

Bore type	full flow, smooth bore
Liner material	NBR
Operating temperature	-25°C to +100°C (-13°F to 212°F)
Max. available length	60m (200ft)



Features & Comments

- Hoses with a temperature rating of -30°C to +121°C and -40°C to +82°C are available upon request
- Handling instructions: ContiTech TKO ASO and AS3 latest edition

Technical Data

Inside Diameter		Rated Working Pressure		Test Pressure		Safety Factor (WP)	Outer Diameter		MBR (storage)		MBR (operation)		Weight	
mm	in	bar	psi	bar	psi		mm	in	m	ft	m	ft	kg/m	lb/ft
51	2.0	345	5000	690	7500	2.5	104	4.1	0.6	2.0	0.7	2.3	15	10
		690	10000	1035	15000	2.25	123	4.8	0.9	3.0	1.0	3.3	27	18
		1035	15000	1552	22500	2.25	140	5.5	1.1	3.6	1.4	4.6	40	27
64	2.5	345	5000	690	7500	2.5	111	4.4	0.6	2.0	0.7	2.3	15	10
		690	10000	1035	15000	2.25	136	5.6	1.0	3.3	1.1	3.6	31	21
		1035	15000	1552	22500	2.25	153	6.0	1.2	3.9	1.5	4.9	45	30
76	3.0	345	5000	690	7500	2.5	126	5.0	0.7	2.3	0.8	2.6	18	12
		690	10000	1035	15000	2.25	148	5.8	1.1	3.6	1.2	3.9	34	23
		1035	15000	1552	22500	2.25	166	6.5	1.4	4.6	1.6	5.3	53	36
		1380	20000	2070	30000	2.25	210	8.3	1.6	5.3	1.6	5.3	109	73
102	4.0	345	5000	690	7500	2.5	166	6.5	1.0	3.3	1.2	3.9	33	22
		690	10000	1035	15000	2.25	192	7.6	1.5	4.9	1.7	5.6	61	41
		1035	15000	1552	22500	2.25	222	8.7	1.4	4.6	1.4	5.0	108	73