

Tauro™Fit Preformed Production Lines

Standard
API Spec. 17K



Construction

Bore type	full flow, rough bore
Liner type	H ₂ S resistant HNBR
Shape	preformed
Operating temperature	-30°C to +90°C (-22°F to 194°F)

Features & Comments

- Further sizes are available upon request
- Easy installation in confined spaces
- Extended service life as a result of reduced risk of over-bending and reduced stress on hose body and on coupling
- Transfers less load to adjacent equipment or pipe work
- Short coupling design increases flexible length with no reduction in bonding strength
- Opens up new design opportunities to reduce the size and weight of oil field equipment
- Coupling materials meet NACE MR 01-75 / ISO 15156 latest edition
- Material of the end fittings is either carbon steel or duplex
- Material of the internal carcass is either 316L or 254 SMO
- Handling instructions: ContiTech TKO ASO and AS4 latest edition



Technical Data

Inside Diameter		Type	Rated Working Pressure		Test Pressure		Safety Factor (WP)	Outer Diameter		MBR (operation)		Weight	
mm	in		bar	psi	bar	psi		mm	in	m	ft	kg/m	lb/ft
102	4.0	Standard	138	2,000	207	3,000	2.25	182	7.2	0.6	2.0	41	28
		Standard c/w st. st. wrap						188	7.4	0.6	2.0	48	32
		Fire rated						203	8.0	0.6	2.0	52	35
		Fire rated c/w st. st. wrap						209	8.2	0.6	2.0	60	40
127	5.0	Standard	138	2,000	776	3,000	2.25	209	8.2	0.7	2.3	49	33
		Standard c/w st. st. wrap						214	8.4	0.7	2.3	57	38
		Fire rated						229	9.0	0.7	2.3	62	42
		Fire rated c/w st. st. wrap						235	9.3	0.7	2.3	70	47
152	6.0	Standard	138	2,000	776	3,000	2.25	238	9.4	0.8	2.6	60	40
		Standard c/w st. st. wrap						244	9.6	0.8	2.6	69	46
		Fire rated						258	10.2	0.8	2.6	74	50
		Fire rated c/w st. st. wrap						264	10.4	0.8	2.6	84	56